

Pickle Degreaser SLOTOCLEAN CR

Pickle Degreaser SLOTOCLEAN CR helps to solve difficult pickling problems. Therefore, Pickle Degreaser SLOTOCLEAN CR isn't only suitable as a pickle degreaser but due to its activating components it also contributes in finding solutions for stubborn pickling tasks, like the degreasing of scale, burned-in fats and oils or to some extent oil carbon. The Pickle Degreaser SLOTOCLEAN CR is based on two liquid components and is usually applied in combination with common hydrochloric or sulphuric acid based pickles. A suitable tenside combination ensures the removal of grease- respectively oil residues and enables fast pickling action by the acid. An additional active component supports the pickling effect without a considerable attack on the base material.

Pickle Degreaser SLOTOCLEAN CR doesn't contain alkylphenoethoxylate and is free of complexing agents and AOX.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read this instruction carefully prior to the use of the process and carefully follow all the parameters that have a direct influence on the operation. We reserve the right to make technical changes. In the interest of safety, please pay attention to the hazard warnings on the labels of the containers. The minimum shelf life of the products is included on the labels and is also available in the appropriate Quality Assurance (QA03).

The current IMDS number of the layer deposited from the process is available on the internet at www.schloetter.com/downloads.

For the storage of chemical products the TRGS 510 must be followed.

If the additives used in this process contain a SVHC-substance, then this will be specified in the corresponding Material Safety Data Sheet, section 15.

