

Pickle Degreaser

SLOTOCLEAN BEF 1790

Removes undesirable surface layers as well as contamination like rust, scale and oxide layers. Especially suitable for high-tensile steel. Very high inhibition value.

APPLICATION

- Universally applicable

PROCESS

- “Two in One” for pickling and deoiling respectively degreasing of parts
- Produces a metallically clean surface for the subsequent plating process

BENEFITS

- Reduces the drag-in of hydrogen peroxide into the base material
- Very low pickling attack, very high service life, low hydrogen embrittlement

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance only. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read this instruction carefully prior to the use of the process and carefully follow all the parameters that have a direct influence on the operation. We reserve the right to make technical changes. In the interest of safety, please pay attention to the hazard warnings on the labels of the containers. The minimum shelf life of the products is included on the labels and is also available in the appropriate Quality Assurance (QA03).

The current IMDS number of the layer deposited from the process is available on the internet at www.schloetter.com/downloads.

For the storage of chemical products the TRGS 510 must be followed.

If the additives used in this process contain a SVHC-substance, then this will be specified in the corresponding Material Safety Data Sheet, section 15.

