

Micro Etch SLOTETCH 584

Micro Etch SLOTETCH 584 has been specifically designed for the pre-treatment of printed circuit boards (PCB), integrated circuit lead frames (IC Frames), copper and Alloy 42 (Ni/Fe) base material.

Micro Etch SLOTETCH 584 is equally suited for use both in through hole plating (PTH) and all stages of pattern plating in the PCB manufacturing.

Micro Etch SLOTETCH 584

- ensures a consistent etch rate
- has a long service life
- is easy to maintain
- is economical to use

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read this instruction carefully prior to the use of the process and carefully follow all the parameters that have a direct influence on the operation. We reserve the right to make technical changes. In the interest of safety, please pay attention to the hazard warnings on the labels of the containers. The minimum shelf life of the products is included on the labels and is also available in the appropriate Quality Assurance (QA03).

The current IMDS number of the layer deposited from the process is available on the internet at www.schloetter.com/downloads.

For the storage of chemical products the TRGS 510 must be followed.

If the additives used in this process contain a SVHC-substance, then this will be specified in the corresponding Material Safety Data Sheet, section 15.

