

Degreaser

SLOTOCLEAN AK 1070

The Degreaser SLOTOCLEAN AK 1070 is a weakly alkaline cleaner for degreasing of cleaning of aluminum, aluminum alloys and zinc die cast. To remove paste from polished zinc die cast a support by ultrasonic is necessary.

Degreaser SLOTOCLEAN AK 1070 is also suitable for degreasing of copper and brass, and to a certain extent for steel.

An outstanding feature of Degreaser SLOTOCLEAN AK 1070 is the low-foaming operation from a temperature of 60 - 70 °C. Therefore, it's also suitable for application in spray installations. This feature is getting lost by the addition of cleaning enhancers (tensides). Therefore, the use of degreaser additives should be avoided in this process.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read this instruction carefully prior to the use of the process and carefully follow all the parameters that have a direct influence on the operation. We reserve the right to make technical changes. In the interest of safety, please pay attention to the hazard warnings on the labels of the containers. The minimum shelf life of the products is included on the labels and is also available in the appropriate Quality Assurance (QA03).

The current IMDS number of the layer deposited from the process is available on the internet at www.schloetter.com/downloads.

For the storage of chemical products the TRGS 510 must be followed.

If the additives used in this process contain a SVHC-substance, then this will be specified in the corresponding Material Safety Data Sheet, section 15.

