

# Wetting Agent AZN

The Wetting Agent AZN is a liquid blend of tensides, primarily used in electrolytic degreasing electrolytes as a spray suppressant. It's also used for replenishment of the tenside content in electrolytic degreasing electrolytes. Wetting Agent AZN also has limited use in alkaline cyanide and alkaline cyanide-free zinc electrolytes.

The Wetting Agent AZN produces a thin layer of dense foam. This prevents spray losses of degreaser solutions or zinc electrolytes respectively.

Depending on the dosing quantity, the cleaning action of the electrolytic degreasers will also be improved.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

## Important:

Please read this instruction carefully prior to the use of the process and carefully follow all the parameters that have a direct influence on the operation. We reserve the right to make technical changes. In the interest of safety, please pay attention to the hazard warnings on the labels of the containers. The minimum shelf life of the products is included on the labels and is also available in the appropriate Quality Assurance (QA03).

The current IMDS number of the layer deposited from the process is available on the internet at [www.schloetter.com/downloads](http://www.schloetter.com/downloads).

For the storage of chemical products the TRGS 510 must be followed.

**If the additives used in this process contain a SVHC-substance, then this will be specified in the corresponding Material Safety Data Sheet, section 15.**

