

Post-Dip Solution SLOTOFIN 90

The Post-Dip Solution SLOTOFIN 90 is used for post-treatment of passivated zinc- and zinc alloy surfaces.

After drying, a clear transparent protective layer is obtained which is resistant to both fingerprinting as well as corrosion and improves the optical appearance. The post-dip solution moves evenly on the parts and leaves no film or unsightly drop-shaped residues.

By the treatment with Post-Dip Solution SLOTOFIN 90, blue passivated zinc and transparent passivated zinc alloy coatings result in a uniform almost transparent appearance.

A hot-soak degreaser combined with suitable degreasing additives can remove post-dip residues from racks or centrifuge baskets. Therefore, we recommend the products of our SLOTOCLEAN series.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read this instructions carefully prior to the use of the process and carefully follow all the parameters that have a direct influence on the operation. We reserve the right to make technical changes. In the interest of safety, please pay attention to the hazard warnings on the labels of the containers. The minimum shelf life of the products is included on the labels and is also available in the appropriate Quality Assurance (QA03).

The current IMDS number of the layer deposited from the process is available on the internet at www.schloetter.com/downloads.

For the storage of chemical products the TRGS 510 must be followed.

If the additives used in this process contain a SVHC-substance, then this will be specified in the corresponding Material Safety Data Sheet, section 15.

