

Pickle Degreaser SLOTOCLEAN BEF 40

Pickle Degreaser SLOTOCLEAN BEF 40 is used with hydrochloric-, sulphuric- or mixed acid based pickles. Excellent degreasing behaviour even on heavily oiled parts is the feature of Pickle Degreaser SLOTOCLEAN BEF 40. Furthermore this product contains inhibitors preventing acids from excessive etching of the base material.

Preferably used are pre-treatment lines where degreasing and pickling is performed concurrently and which don't have a separate pre-degreasing station. The make-up concentration of Pickle Degreaser SLOTOCLEAN BEF 40 depends on the assigned task. Heavily oiled parts higher make-up quantities are used and vice versa.

The Pickle Degreaser SLOTOCLEAN BEF 40 does not contain alkylphenolethoxylate and is AOX free. However, when operated with hydrochloric acid AOX may be formed.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance only. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read this instruction carefully prior to the use of the process and carefully follow all the parameters that have a direct influence on the operation. We reserve the right to make technical changes. In the interest of safety, please pay attention to the hazard warnings on the labels of the containers. The minimum shelf life of the products is included on the labels and is also available in the appropriate Quality Assurance (QA03).

The current IMDS number of the layer deposited from the process is available on the internet at www.schloetter.com/downloads.

For the storage of chemical products the TRGS 510 must be followed.

If the additives used in this process contain a SVHC-substance, then this will be specified in the corresponding Material Safety Data Sheet, section 15.

