

Degreaser SLOTOCLEAN AK 150

Degreaser SLOTOCLEAN AK 150 is a strongly alkaline process for immersion degreasing of steel. The Degreaser Salt SLOTOCLEAN AK 151 contains sodium hydroxide, is low in silicate and doesn't contain phosphates or complexing agents.

Degreaser SLOTOCLEAN AK 150 is especially suitable for the removal of processing oil suitable and can be used for both rack- and barrel applications.

Although the Degreaser SLOTOCLEAN AK 150 does already contain surfactants, the additional use of a degreaser additive may be required for a heavy load by greases and oils. Schlötter offers a wide range of additives to enhance cleaning. Please refer to technical data sheet BATH 02300-E Summary Degreaser Additives about the different possible combinations.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read this instruction carefully prior to the use of the process and carefully follow all the parameters that have a direct influence on the operation. We reserve the right to make technical changes. In the interest of safety, please pay attention to the hazard warnings on the labels of the containers. The minimum shelf life of the products is included on the labels and is also available in the appropriate Quality Assurance (QA03).

The current IMDS number of the layer deposited from the process is available on the internet at www.schloetter.com/downloads.

For the storage of chemical products the TRGS 510 must be followed.

If the additives used in this process contain a SVHC-substance, then this will be specified in the corresponding Material Safety Data Sheet, section 15.

