

# Degreaser

## SLOTOCLEAN AK 170

Degreaser SLOTOCLEAN AK 170 is a strong alkaline process which cannot only be used for electrolytic degreasing but also for immersion degreasing of steel. The process is particularly suitable for the removal of process oils and its features are good wetting- and rinsing behaviour.

Degreaser SLOTOCLEAN AK 170 is operated with two components: Degreaser Salt SLOTOCLEAN AK 171 and a degreaser additive/cleaning enhancer according to the assigned task. Schlötter offers a wide range of additives to enhance cleaning. Our Summary Degreaser Additives (BATH 02300-E) informs you about the different possible combinations.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

### Important:

Please read this instruction carefully prior to the use of the process and carefully follow all the parameters that have a direct influence on the operation. We reserve the right to make technical changes. In the interest of safety, please pay attention to the hazard warnings on the labels of the containers. The minimum shelf life of the products is included on the labels and is also available in the appropriate Quality Assurance (QA03).

The current IMDS number of the layer deposited from the process is available on the internet at [www.schloetter.com/downloads](http://www.schloetter.com/downloads).

For the storage of chemical products the TRGS 510 must be followed.

**If the additives used in this process contain a SVHC-substance, then this will be specified in the corresponding Material Safety Data Sheet, section 15.**

