

Degreaser

SLOTOCLEAN AK 380

Degreaser SLOTOCLEAN AK 380 is a strong alkaline immersion degreaser for steel. It is also suitable for cleaning of copper and its alloys. It must however be observed that brass may tarnish with extended treatment times. Zinc and aluminium are attacked.

Make-up and the replenishment is performed with only one component which contains all the necessary components for the operation.

The tenside combination of Degreaser SLOTOCLEAN AK 380 acts demulsifying. It's therefore especially suitable for plants with gravity oil separators respectively ultrafiltration systems. The addition of further tensides in the form of degreaser additives is therefore not advised.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read this instruction carefully prior to the use of the process and carefully follow all the parameters that have a direct influence on the operation. We reserve the right to make technical changes. In the interest of safety, please pay attention to the hazard warnings on the labels of the containers. The minimum shelf life of the products is included on the labels and is also available in the appropriate Quality Assurance (QA03).

The current IMDS number of the layer deposited from the process is available on the internet at www.schloetter.com/downloads.

For the storage of chemical products the TRGS 510 must be followed.

If the additives used in this process contain a SVHC-substance, then this will be specified in the corresponding Material Safety Data Sheet, section 15.

